Introduction

This installation guide provides installation and removal instructions. To receive a copy of the instruction manual, contact your local Fisher Sales Office or Sales Representative or view a copy at www.FISHERregulators.com. For further information refer to:

P590 Series Instruction Manual, form 5289, D101555X012.

P.E.D. Categories

This product may be used as a safety accessory with pressure equipment in the following Pressure Equipment Directive 97/23/EC categories. It may also be used outside of the Pressure Equipment Directive using sound engineering practice (SEP) per table below.

PRODUCT SIZE	CATEGORIES	FLUID TYPE
DN 6 (1/4-inch)	SEP	1

Specifications

Maximum Working Pressures(1)

Brass: 96,6 bar (1400 psig) Aluminum: 41,1 bar (600 psig)

Proof Test Pressure

All Pressure Retaining Components have been proof tested per Directive 97/23/EC - Annex 1, Section 7.4

Installation

WARNING

Personal injury, equipment damage, or leakage due to escaping fluid or bursting of pressure-containing parts may result if the filter is installed where its capabilities can be exceeded or where conditions exceed any ratings of the adjacent piping or piping connections. To avoid this, install a filter where:

- Service conditions are within unit capabilities.
- Service conditions are within applicable codes, regulations, or standards.

Taking Out of Service (Shutdown)

WARNING

To avoid personal injury resulting from sudden release of pressure, isolate the regulator/filter from all pressure and cautiously release trapped pressure from the regulator/filter before attempting disassembly.

^{1.} The pressure/temperature limits in this installation guide and any applicable standard or code limitation should not be exceeded.





Parts List

Key Description

1 Filter Body

Type P595, P594-1, brass

Type P593-1,

aluminum

aluminum (NACE)

- 2 Filter Element
- 3 Filter Head
- 4 Machine Screw
- 5 Washer
- 6 Spring Washer
- 7 Gasket




Figure 1. Typical P590 Series Filter Assembly

©Fisher Controls International, Inc., 2002; All Rights Reserved

Fisher and Fisher Regulators are marks owned by Fisher Controls International, Inc. The Emerson logo is a trade mark and service mark of Emerson Electric Co. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. We reserve the right to modify or improve the designs or specifications of such products at any time without notice.

For information, contact Fisher Controls, International: Within USA (800) 588-5853 - Outside USA (972) 542-0132 France - (33) 23-733-4700 Singapore - (65) 770-8320 Mexico - (52) 57-28-0888

