





High Performance Digital Valve Control Made Easy



TEC2 Key Benefits:

- Actuator size expanded range for small valves new Model 500, smallest, lightest multi-turn actuator frame size
- Advanced configuration, diagnostics and predictive capability through DCMLink software platform with integration path to AMS Device Manager, Delta V, Emerson PlantWeb
- Ease of Use and Service Multiple languages, improved graphical display, patented remote module
- Non-Intrusive design & rugged ductile iron gear housing is shock and vibration-resistant
- Non-penetrating, vibration-resistant hall effect switches enable setup without opening control compartments
- Discrete, analog and digital controls availability
- Open network control for a wide range of topologies and protocols, including Modbus RTU, Profibus, FOUNDATION™ Fieldbus, DeviceNet™, Ethernet, HART™ and Wireless HART™

Model 500

In addition to an innovative control platform, TEC2 extends the proven and reliable mechanical frame family to include Model 500, the latest smaller and lightweight multiturn actuator frame size designed to meet application needs requiring lower torque ranges. Model 500 offers full functionality, including increased stem acceptance of existing TEC actuators with a compact design and enhanced electronic features. It also comes with multiple display language options, data logging, Bluetooth™ and full network protocol support.

TEC2

Proven Bettis technology in electric actuation coupled with simplified digital controls, TEC2 is the next step in reliable high-performance digital valve control to make your work easier and safer.

Enhanced data-logging feature with time and date stamp features provide you with information to make effective and timely preventive maintenance decisions.

TEC2* Certifications:


- F.M., C.S.A., CE, IECEX, GOST, InMetro, CEPEL, AWWA C542, ATEX
- Shock & Vibration (MIL-STD-167-1, MIL-STD-901D)
- IP68 certified for submersible applications (50 ft, 7 days)
- SI



*Model 500 enclosure certification pending agency approval *SIL approval pending



More Flexibility And Reliability Through Innovative Product Design



New Model 500. More compact, lighter weight model with larger stem acceptance is ideal for smaller valves



Accurate torque sensing using rotary Hall-Effect encoder directly connected to torque pinion is active in both motor and manual operation



Compact profile Patented Remote Display Module puts local controls within easy access. Safely operate, configure or access diagnostics when actuator is hard or impossible to access

Simplified Intelligence, When You Need It, Where You Need It



Absolute Position Detector provides precise valve position under all conditions including loss of power, no battery backup required




Separate Terminal Chamber. Dual sealed separate terminal chamber with highly legible terminal markings and pre-installed screws eases field wiring. Primary fuses accessible without opening controls compartments



Process trends measured and recorded. Historical logs can reveal process trends to help with maintenance intervals and improve the timeliness of predictive maintenance enhanced with the use of DCMLink™ software

Maximize Plant Efficiency And Worker Safety Every Time




Programmable monitoring. Performance data can be monitored to fix current problems and recorded to analyze future issues





Calibration and operation from a safe and convenient location. Patented Remote Display Module (RDM) allows you to control and monitor the actuator up to 4000 ft (1.2 km) away. Ideal for hazardous environment


Reliable Process Insight For Every Application



Prevent untimely operation with a built-in inhibitor interlock system that prevents operation with other devices until external contact has been made. Your systems can now coordinate with each other



Your displays need to show the right information without being too simple or complex. Easy to read IconoText displays and icons allow for an easy and intuitive setup



Configurable process alarms are standard; TEC2 will alert you of any issues in your process and alarms can also be set to trigger open or close functions

World Area Configuration Centers (WACC) offer sales support, service, inventory and commissioning to our global customers. Choose the WACC or sales office nearest you:

NORTH & SOUTH AMERICA

19200 Northwest Freeway Houston TX 77065 USA

T +1 281 477 4100 F +1 281 477 2809

Av. Hollingsworth 325 Iporanga Sorocaba SP 18087-105 Brazil T+55 15 3238 3788

F +55 15 3238 3788 F +55 15 3228 3300

ASIA PACIFIC

No. 9 Gul Road #01-02 Singapore 629361 T+65 6777 8211 F+65 6268 0028

No. 1 Lai Yuan Road Wuqing Development Area Tianjin 301700 P. R. China T +86 22 8212 3300 F +86 22 8212 3308

MIDDLE EAST & AFRICA

P. O. Box 17033 Dubai United Arab Emirates T +971 4 811 8100 F +971 4 886 5465

P. O. Box 10305 Jubail 31961 Saudi Arabia T +966 3 340 8650 F +966 3 340 8790

24 Angus Crescent Longmeadow Business Estate East P.O. Box 6908 Greenstone 1616 Modderfontein Extension 5 South Africa T+27 11 451 3700 F+27 11 451 3800

EUROPE

Berenyi u. 72-100 Videoton Industry Park Building #230 Székesfehérvár 8000 Hungary T +36 22 53 09 50 F +36 22 54 37 00

For complete list of sales and manufacturing sites, please visit www.emerson.com/actuationtechnologieslocations or contact us at info.actuationtechnologies@emerson.com



For complete technical and installation documentation, scan QR.



 $\ \ \, \mathbb{C}$ 2017 Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Bettis™ is a mark of the Emerson family of companies. All other marks are property of their respective owners.



